

# Attache-câbles SES®-QUICK SE

crantage extérieur

PA 6.6 naturel





SES®-QUICK

-40 à +85°C



## • Attaches SE à crantage extérieur

type	code article	dimensions long. x largeur mm	Ø de serrage maxi. (mm)	force de serrage mini. (daN)	
110/26 SE-C	0186 0603 018	110 x 2,6	24	8	100
125/47 SE-C	0186 0070 018	125 x 4,7	26	22	100
160/47 SE-C	0186 0075 018	160 x 4,7	38	22	100
185/47 SE-C	0186 0080 018	185 x 4,7	47	22	100
300/47 SE-C	0186 0085 018	300 x 4,7	80	22	100
370/47 SE-C	0186 0090 018	370 x 4,7	105	22	100
210/76 SE-C	0186 0672 018	210 x 7,6	52	53	100
300/76 SE-C	0186 0682 018	300 x 7,6	80	53	100
370/76 SE-C	0186 0686 018	370 x 7,6	103	53	100
175/90 SE-C	0186 0573 018	175 x 9	42	79	100
260/90 SE-C	0186 0576 018	260 x 9	69	79	100
360/90 SE-C	0186 0578 018	360 x 9	102	79	100
550/90 SE-C	0186 0082 018	550 x 8,9	155	79	100
780/90 SE-C	0186 0088 018	775 x 8,9	230	79	100



Homologué SNCF selon la NFF 61-349