


Montage de raccord
Connector assembly



Portrait

Gaines annelées
ROHRflex

Raccords
FLEXAquick

N° FLEXA	DE OD									
noir black	ø			ø I mm	ø B mm	C mm	D mm	SW mm	kg/100	Pce Pcs.
RQG-C		CTG JIS B 0204	Whitworth DIN ISO 228-1							[IP 68 / 69K]
5020.052.208	10,0		1/4"	7,0	17,0	10,0	32,5	16	0,400	50
5020.052.212	13,0		1/4"	9,0	20,0	10,0	35,0	18	0,520	50
5020.052.209	13,0		3/8"	10,0	21,0	10,0	35,0	18	0,500	50
5020.052.201	13,0	G 16	1/2 "	13,0	27,0	14,0	39,5	18	0,660	50
5020.052.210	15,8		3/8"	12,5	23,0	10,0	37,0	21	0,640	50
5020.052.202	15,8	G 16	1/2"	12,5	27,0	13,5	41,5	21	0,760	50
5020.052.203	21,2	G 16	1/2"	16,0	29,5	13,0	45,5	27	1,140	50
5020.052.204	28,5	G 22	3/4"	20,5	37,0	13,0	48,0	34	1,720	25
5020.052.205	34,5	G 28	1"	25,5	44,0	16,0	52,0	40	2,280	25
5020.052.206	42,5	G 36	1 1/4 "	35,0	52,0	18,0	59,0	60	3,080	25
5020.052.211	54,5		1 1/2"	40,0	40,0	17,0	89,0	70	4,400	10
5020.052.207	54,5	G 54	2"	49,0	64,0	18,0	89,0	70	4,500	10
RQG-N			NPT ANSI/ASME B1.20.1							[IP 68 / 69K]
5020.056.201	10,0		1/4"	7,0	17,0	11,5	34,0	16	0,420	50
5020.056.202	13,0		1/4"	10,0	20,0	12,0	37,0	18	0,560	50
5020.056.203	13,0		3/8"	10,0	20,0	12,0	37,0	18	0,540	50
5020.056.204	15,8		3/8"	12,5	23,0	12,0	39,0	21	0,600	50
5020.056.205	15,8		1/2"	12,5	25,0	12,0	39,0	21	0,720	50
5020.056.206	21,2		1/2"	17,0	29,5	13,0	43,5	27	1,140	50
5020.038.221	28,5		3/4"	21,0	37,0	14,0	47,5	34	1,680	25
5020.038.227	34,5		1"	27,5	44,0	16,0	52,0	40	2,200	25
5020.056.207	42,5		1 1/4"	36,5	52,0	18,0	77,0	60	1,520	25
5020.056.208	42,5		1 1/2"	36,5	55,0	18,0	77,0	60	3,500	25
5020.056.209	54,5		1 1/2"	42,5	64,0	18,0	89,0	70	4,400	10
5020.056.210	54,5		2"	48,5	64,0	21,0	92,0	70	4,500	10

