



**Raccord droit rapide, synthétique
filetage extérieur en laiton nickelé
décharge de traction
haute étanchéité**

- résistant à l'huile et l'essence
- largement résistant aux acides et solvants
- sans silicone, cadmium et halogène
- résistance élevée aux contraintes mécaniques
- résistant aux impacts
- couple élevé du raccord fileté
- serrage et étanchéité optimaux des câbles

Pour assurer un indice de protection élevé entre le presse-étoupe et le corps du raccord, il est nécessaire d'utiliser une masse d'étanchéité (voir norme 1015 de la société FLEXA).

**Plastic connector, quick-type
straight
outer thread made of nickel-plated brass
strain relief, high sealing rate**

- resistant against oil and benzine
- widely resistant to acids and solvents
- free of silicone, cadmium, halogen
- fit for high mechanical stress
- impact-resistant
- high torque of thread connection
- optimal held and sealing of cables at the same time

To ensure a high protection system, IP 68, at the thread between cable gland insert and screw connector housing it is necessary to use a sealing compound (FLEXA company standard 1015 A).

| N° FLEXA | N° FLEXA | | DE OD | | | | | | | | | | |
|----------------|------------------|-----------|-------------|------------------|------|------|------|-------|-----|--------|--------|----------------------|--|
| noir black | gris * grey * | | ø | ø I | ø B | C | D | SW1 | SW2 | kg/100 | Pce | | |
| | | mm | mm | mm | mm | mm | mm | mm | mm | | Pcs. | | |
| RQGKZ-M | | | | métr. | | | | | | | | [IP 68 / 69K] | |
| | | | | EN 60423 | | | | | | | | | |
| 5110.010.212 | 5110.010.012 | 3,0- 5,3 | 10,0 | M 12 | 6,5 | 20,0 | 5,0 | 53,5 | 18 | 14 | 2,240 | 50 | |
| 5110.013.216 | 5110.013.016 | 5,0- 8,5 | 13,0 | M 16 | 10,0 | 24,0 | 5,0 | 55,0 | 22 | 17 | 3,380 | 50 | |
| 5110.015.220 | 5110.015.020 | 7,5-10,0 | 15,8 | M 20 | 13,5 | 27,0 | 6,0 | 63,0 | 25 | 22 | 3,500 | 50 | |
| 5110.021.220 | 5110.021.020 | 10,0-12,5 | 21,2 | M 20 | 13,5 | 29,5 | 6,0 | 65,0 | 28 | 22 | 5,600 | 25 | |
| 5110.021.225 | 5110.021.025 | 9,0-16,0 | 21,2 | M 25 | 16,5 | 33,0 | 7,0 | 70,0 | 31 | 27 | 6,100 | 25 | |
| 5110.028.225 | 5110.028.025 | 11,0-16,0 | 28,5 | M 25 | 16,5 | 37,0 | 7,0 | 70,0 | 31 | 27 | 8,500 | 25 | |
| 5110.028.232 | 5110.028.032 | 12,0-16,0 | 28,5 | M 32 | 21,0 | 43,0 | 8,0 | 75,0 | 31 | 34 | 13,400 | 25 | |
| 5110.034.232 | 5110.034.032 | 14,5-20,5 | 34,5 | M 32 | 22,0 | 44,0 | 8,0 | 75,0 | 42 | 34 | 13,400 | 25 | |
| 5110.034.240 | 5110.034.040 | 19,0-20,5 | 34,5 | M 40 | 27,5 | 48,0 | 8,0 | 78,0 | 42 | 43 | 14,000 | 25 | |
| 5110.042.240 | 5110.042.040 | 21,0-26,0 | 42,5 | M 40 | 28,0 | 58,0 | 8,0 | 107,0 | 55 | 43 | 19,000 | 10 | |
| 5110.042.250 | 5110.042.050 | 20,0-26,5 | 42,5 | M 50 | 36,0 | 58,0 | 9,0 | 109,0 | 55 | 55 | 16,000 | 10 | |
| 5110.054.250 | 5110.054.050 | 25,0-35,0 | 54,5 | M 50 | 36,0 | 68,0 | 9,0 | 120,0 | 65 | 55 | 31,700 | 10 | |
| 5110.054.263 | 5110.054.063 | 32,0-42,0 | 54,5 | M 63 | 44,0 | 68,0 | 10,0 | 139,0 | 65 | 65 | 34,000 | 10 | |
| RQGKZ-P | | | | PG | | | | | | | | [IP 68 / 69K] | |
| | | | | DIN 40430 | | | | | | | | | |
| 5500.010.207 | | 3,0- 6,0 | 10,0 | 7 | 6,8 | 20,5 | 5,0 | 50,0 | 18 | 14 | 2,740 | 50 | |
| 5500.013.209 | | 3,0- 8,0 | 13,0 | 9 | 8,5 | 24,0 | 6,0 | 56,5 | 22 | 17 | 2,600 | 50 | |
| 5500.015.211 | | 5,0-10,0 | 15,8 | 11 | 10,5 | 27,0 | 6,0 | 57,0 | 25 | 20 | 3,500 | 50 | |
| 5500.021.216 | | 11,0-14,0 | 21,2 | 16 | 14,8 | 33,0 | 6,5 | 65,0 | 31 | 24 | 5,120 | 25 | |
| 5500.028.221 | | 12,0-18,0 | 28,5 | 21 | 18,5 | 41,0 | 7,0 | 71,0 | 39 | 30 | 8,480 | 25 | |
| 5500.034.229 | | 19,0-25,0 | 34,5 | 29 | 25,5 | 48,5 | 8,0 | 75,0 | 46 | 40 | 13,280 | 25 | |
| 5500.042.236 | | 25,0-33,0 | 42,5 | 36 | 34,5 | 58,0 | 9,0 | 103,0 | 55 | 50 | 17,800 | 10 | |
| 5500.054.248 | | 35,0-43,0 | 54,5 | 48 | 44,0 | 68,0 | 10,0 | 120,0 | 65 | 64 | 29,800 | 10 | |

* gris - Délai de livraison sur demande
* grey - delivery time on request