




PRESSE-ETOUPE **MAXIinox**

en Acier Inox 303 (X8 CrNiS 18-9)
en Acier Inox 316L (X2 CrNiMo 17-12-2)

7900 7900A



MAXIinox en Acier Inox AISI 303

Filetage Pg DIN 40 430

Référence Acier Inox AISI 303	P	Trou de fixation (mm)	Ø A min-max (mm)	B Clef (mm)	E (mm)	C (mm)	L min-max (mm)	Cond. ^t
7900.07	Pg 7	12,7	3 - 7	16	18	5,0	16-20	90/30
7900.09	Pg 9	15,5	4 - 8	17	19	6,0	17-23	90/30
7900.11	Pg11	18,8	4,5-10	20	23	6,0	20-25	60/30
7900.13	Pg13,5	20,5	5 -12	22	25	6,5	20-26	90/30
7900.16	Pg16	22,6	7 -13	24	27	6,5	20-27	60/30
7900.21	Pg21	28,5	10 -17	30	33	7,0	24-30	40/20
7900.29	Pg29	37,2	17 -25	40	45	8,0	30-37	30/15
7900.36	Pg36	47,2	20 -32	50	55	8,0	38-48	10
7900.42	Pg42	54,2	28 -38	57	63	10,0	36-46	5
7900.48	Pg48	60,0	34 -45	67	74	15,0	40-52	5

Matière: ACIER INOX 303/316L

Garniture: NEOPRENE®

Griffe de serrage:

POLYAMIDE PA6.6

Joint: NITRILE 70 sh A

(pré-monté)

Étanchéité: IP 68

Température d'utilisation:

de -25°C à +100°C (continue)

MAXIinox en Acier Inox AISI 316L

Filetage Pg DIN 40 430

Référence Acier Inox AISI 316L	P	Trou de fixation (mm)	Ø A min-max (mm)	B Clef (mm)	E (mm)	C (mm)	L min-max (mm)	Cond. ^t
7900A.07	Pg 7	12,7	3 - 7	16	18	5,0	16-20	60/20
7900A.09	Pg 9	15,5	4 - 8	17	19	6,0	17-23	60/20
7900A.11	Pg11	18,8	4,5-10	20	23	6,0	20-25	100/20
7900A.13	Pg13,5	20,5	5 -12	22	25	6,5	20-26	100/20
7900A.16	Pg16	22,6	7 -13	24	27	6,5	20-27	40/20
7900A.21	Pg21	28,5	10 -17	30	33	7,0	24-30	60/15
7900A.29	Pg29	37,2	17 -25	40	45	8,0	30-37	20/10
7900A.36	Pg36	47,2	20 -32	50	55	8,0	38-48	7
7900A.42	Pg42	54,2	28 -38	57	63	10,0	36-46	5
7900A.48	Pg48	60,0	34 -45	67	74	15,0	40-52	5

